
TRA TRA/G






Rectangular and electrically heated ironing table, with or without boiler

- Utility vacuum table with electrically heated board
- Adjustable temperature of the board by means of a thermostat
- Built-in single phase vacuum unit
- Available either with STANDARD or with MAXI board
- Steam iron assembly included in the version with boiler





Technical Specifications	TRA (1300x800) TRA AF (1300x800)	TRA (1600x800) TRA AF (1600x800)	TRA/G * (1300x800)	TRA/G * (1600x800)
Voltage	230V/400V/1/50-60 Hz	230V/400V/1/50-60 Hz	230V/400V/1-3/50-60 Hz	230V/400V/1-3/50-60 Hz
Boiler heater			3.3-3.9-4.8 kW	3.3-3.9-4.8 kW
Iron heater	0,830 kW	0,830 kW	0,830 kW	0,830 kW
Board heater	1-1,5 kW	1-1,5 kW	1 kW	1,5 kW
Suction motor	0,45 kW	0,45 kW	0,45 kW	0,45 kW
Steam pressure			2,8 bar	2,8 bar
Water inlet			3/8"	3/8"
Boiler exhaust			3/8"	3/8"
Board dimensions	1300x800 mm	1600x800 mm	1300x800 mm	1600x800 mm
Overall dimensions	1300x840x920 mm	1600x840x920 mm	1300x840x920 mm	1600x840x920 mm
Net weight	108 Kg	113 Kg	132 Kg	142 Kg
Gross weight (cartpallet)	127 Kg		151 Kg	
Gross weight (crate)		180 Kg		209 Kg
Packing dimensions	1330x970x1080 mm	1780x960x1170 mm	1330x970x1080 mm	1780x960x1170 mm
(*) With boiler				

Options

- Swinging arm with suction and heated sleeve shapeSwinging arm with suction and heated egg shape
- Swinging arm with suction and heated egg shapSwinging arm with suction and spotting shape
- Built-in electric and automatic steam boiler with iron
- Water pump (for versions with boiler)
- Steam iron assembly (for versions without boiler)
- Steam gun
- Steam air gun
- Water spray gun with or without support
- Sliding trolley with balancer, with or without lighting - Lighting

The firm reserves the right to make any necessary modification without notice.